UK Patent Application GB GB GB 2195892 GB AV

(43) Application published 20 Apr 1988

(21) Application No 8723121

(22) Date of filing 2 Oct 1987

(30) Priority data

(31) 916062

(32) 5 Oct 1986

(33) US

(71) Applicant

The Procter & Gamble Company

(Incorporated in USA-Ohio)

One Procter & Gamble Plaza, Cincinnati, Ohio 45202, **United States of America**

(72) Inventors

Frances Bernard Chapura Charles Wilson Bishop Kenneth Charaly Philip Floyd Pflaumer **David Lynn Suter**

(51) INT CL* A61K 47/00 9/20 33/06 37/22

(52) Domestic classification (Edition J):

A5B 180 230 232 23Y 26Y 272 273 274 275 27Y 285 28Y 301 303 30Y 340 343 34Y 402 40Y 481 482 48Y

586 58Y 827 832 833 KC U18 1318 1330 A58

(56) Documents cited

GB A 2122489 GB 1336373

GB 1068049 GB 1462443

GB 1380206 GB 0932378

(58) Field of search

Selected US specifications from IPC sub-class A61K

(74) Agent and/or Address for Service Maxim Courtney Brooks, Proctor & Gamble (NTC) Ltd, Whitley Road, Los

Newcastle upon Tyne NE12 9T8

(54) Improving palatability of pharmaceutical chewable tablets

(57) Lipid-containing, molded pharmaceutical compositions comprise:

(a) from about 10% to about 50% of a lipid material having a melting point of from about 26°C to about 37°C;

(b) from about 10% to about 50% of a particulate dispersant material (e.g. a hydrophilic saccharide);

(c) from about 0.1% to about 3% of an emulsifier; and

(d) a safe and effective amount of a pharmaceutical active material. wherein the particulate materials have a mean particle size of from about 4 microns to about 10 microns.

The compositions are described are antacid chewable tablets. wherein the lipid formulation is to improve palatability, and effective dispersion in the mouth and stomach.

GB 0640155

1297

SPECIFICATION

Palatable solid pharmaceutical compositions

	Palatable solid pharmaceutical compositions	
5	BACKGROUND OF THE INVENTION This invention relates to palatable solid pharmaceutical compositions useful in humans and other animals. In particular, it relates to highly efficacious compositions comprising a pharmaceutical active in a lipid-containing matrix. Preferred compositions further relative to highly palatable	5
10	Pharmaceutical compositions may be produced in a variety of dosage forms, depending upon the desired route of administration of the active material. Oral dosage forms, for example, include such solid compositions as tablets, capsules, granules and bulk powders, and such liquid	· 10
15	compositions as solutions, emulsions, and suspensions. The particular dosage form utilized may, of course, depend upon such factors as the solubility and chemical reactivity of the pharmaceutical active. Further, the dosage form may be selected so as to optimize delivery of the pharmaceutical active and/or consumer acceptability of the composition. Tablet compositions offer many advantages, including ease of product handling, chemical and	15
20	physical stability, portability (in particular, allowing ready availability to the consumer when needed), aesthetic acceptability, and dosage precision, (i.e., ensuring consistent and accurate doses of the pharmaceutical active). However, liquid formulations may offer advantages in the treatment of certain disorders, such as disorders of the upper gastrointestinal tract, wherein delivery of an active material dissolved or dispersed in a liquid ensures rapid and complete	20
25	deliver to the afflicted area. In an effort to obtain the therapeutic advantages associated with liquid formulations as well as the broad advantages associated with solids, many chewable tablet formulations have been developed and described in the pharmaceutical literature. See, for example, L. Lachmn, et al., The Theory and Practice of Industrial Pharmacy (2nd Ed., 1976). Many such compositions are antacids, for the treatment of gastric hyperacidity and related	25
30	disorders. Many antacid compositions in liquid form are quite effective due to the ready availability of the antacid active material (which is typically water-insoluble) suspended in a liquid vehicle. There are also many solid antacid formulations, typically chewable tablets, which are designed to deliver small particles of antacid active to the stomach after chewing of the tablet. Chewable tablets, such as antacid tablets, often contain high levels of mannitol or similar	30
35	binders as well as methylcellulose, glycine, or other binding agents. Other chewable tablets are described in the literature containing fatty materials. See, for example, U.S. Patent 4,230,693, Izzo, et al., issued October 28, 1980, U.S. Patent 4,327,076, Puglia, et al., issued April 27, 1982, U.S. Patent 4,327,077, Puglia, et al., issued .\pril 27, 1982, U.S. Patent 4,533,543, Morris, et al., issued August 6, 1985, and U.S. Patent 4,581,381, Morris, et al., issued April 8, 1986.	35
40	Many such solid antacid formulations fail to offer equivalent efficacy to liquid antacid compositions, for a variety of reasons. For example, the tablets may be incompletely chewed due to poor palatability of the composition. This problem is particularly acute with antacids, since the active materials in these products often have a metallic flavor and an astringent, chalky mouth	40
45	feel. Such compositions may also have a gummy texture, and are subject to "taste fatigue", i.e., the composition is perceived to be less palatable after ingestion of multiple doses. Further, the binders and other materials used in such chewable tablets may prevent rapid and effective delivery of active materials to the stomach. It has been found that tablet formulations containing selected lipid materials, emulsifiers and	45
50	particulate materials are highly palatable and effective compositions for the delivery of pharmaceutical active materials. Such compositions afford better taste, mouth feel, and storage stability than compositions known in the art. For example, such compositions containing selected materials with selected particle sizes, and formulated to have a selected product viscosity, afford improved palatability when compared to other lipid containing compositions.	50
55	SUMMARY OF THE INVENTION The present invention provides lipid-containing, molded pharmaceutical compositions, comprising:	55
60	 (a) from about 10% to about 50% of a lipid material having a melting point of from about 26°C to about 37°C; (b) from about 10% to about 50% of a particulate dispersant material; (c) from about 0.1% to about 3% of an emulsifier; and (d) a safe and effective amount of a pharmaceutical active material; 	60

wherein the particulate materials in said composition have a mean particle size of from about 4

microns to about 10 microns, with less than about 10% of said particulates greater than about 30 microns in size. Preferably, the measured viscosity of said composition is less than about 10,000 cps at about 40°C.

Among the preferred lipid-containing compositions of this invention are chewable tablets useful 5 for the treatment of upper gastrointestinal disorders, such as an antacid composition containing from about 10% to 65% of an acid neutralizing material. The present invention also provides coated unit dosage compositions which comprise the lipid-containing solid compositions of this invention coated with a solid coating material.

10 DESCRIPTION OF THE INVENTION

10

The compositions of the present invention contain a pharmaceutical active material in a vehicle containing a lipid base material, a dispersant material and an emulsifier. In addition, the compositions of the present invention may contain optional pharmaceutically-acceptable components which may modify their physical characteristics and/or therapeutic effects. All components of the 15 present compositions must, of course, be pharmaceutically-acceptable. As used herein, a "pharmaceutically-acceptable" component is one which is suitable for use with humans and/or other animals without undue adverse side effects (such as toxicity, irritation and allergic response)

commensurate with a reasonable benefit/risk ratio. The present invention provides lipid-containing, molded pharmaceutical compositions, compris-20 ing:

20

15

- (a) from about 10% to about 50% of a lipid material having a melting point of from about 26°C to about 37°C;
- (b) from about 10% to about 50% of a particulate dispersant material;

(c) from about 0.1% to about 3% of an emulsifier; and

25

(d) a safe and effective amount of a pharmaceutical active material;

wherein the particulate materials in said composition have a mean particle size of from about 4 microns to about 10 microns, with less than about 10% of said particulates greater than about 30 30 microns in size. Preferably, the measured viscosity of said composition is less than about 10,000 cps at about 40°C. Except as otherwise stated, all percentages set forth herein are by weight of total composition.

35

Further, as used herein, the term "safe and effective amount" refers to the quantity of a component which is sufficient to yield a desired therapeutic response without undue adverse 35 side effects (such as toxicity, irritation or allergic response) commensurate with a reasonable benefit/risk ratio when used in the manner of this invention. The specific "safe and effective amount" will, obviously, vary with such factors as the particular condition that is being treated, the severity of the condition, the duration of the treatment, the physical condition of the patient, the nature of concurrent therapy (if any), and the specific formulation and optional components 40 employed.

Preferably, the lipid base material is present in the present compositions at a level of from about 20% to about 40%, more preferably from about 25% to about 40%. Also preferably, the dispersant material is present at a level of from about 20% to about 40%, more preferably from about 20% to about 35%. The emulsifier is preferably present at a level of from about 0.5% to 45 about 2%, more preferably from about 0.6% to about 1.5%. Specific components, and optional materials useful in these chewable tablet compositions are further described below.

These compositions may be provided in unit-dosage form, as molded tablets. Molded tablets are produced by forming a liquid produce mass, i.e., by melting the fatty carrier materials and admixing the other components, followed by pouring into tablet-form molds, and cooling to a 50 solid state. Although these compositions may be swallowed whole or in part without chewing, the present compositions are preferably comprised so as to facilitate chewing and/or melting in the mouth. The present compositions thereby facilitate dispersion of the pharmaceutical active material in saliva and (after swallowing, ultimately) in the gastric fluids of the stomach.

50

55

As described above, the present chewable tablet compositions contain four essential components: a lipid base material, a dispersant material, a nonionic emulsifier material, and a pharmaceutical active material. These compositions may also contain components, such as other emulsifiers, tempering aids, flavorants and colorants.

60

Lipid Material:

60

55 Essential Components

The compositions of the invention contain one or more materials, (herein individually and in mixtures referred to as "lipid materials") that are substantially water-insoluble, inert, pharmaceutically-acceptable hydrocarbon fats or oils, or their derivatives, or mixtures thereof. The lipid 65 materials useful herein preferably have a melting point of from about 26°C (80°F) to about 37°C

	(99°F), preferably from about 32°C (90°F) to about 35°C (95°F), more preferably about 33°C (91°F). (As used herein "melting point" refers to the capillary melting point, at which essentially all of the fat is in a liquid state.) The (70°F), about 52% to 56% solid at about 26°C (80°F), and less than about 1% solid at about 33.5°C (92°F).	
5	· · ·	5
10	October 6, 1986. Such particularly preferred compositions contain one or more materials, herein "lipid base materials", which together with all other mono-, di- and tri-glycerides (if any) in the compositions form the "lipid component" of the chewable tablet compositions. The lipid compo-	10
	nent of the present composition thus preferably contains certain key triglycerides: saturated-oleic-saturated ("SOS"), saturated-unsaturated-unsaturated ("SUU"), unsaturated-unsaturated-unsaturated ("SUU"), saturated-lineolic-saturated ("SLS"), saturated-saturated-oleic ("SSO"), and saturated-	
15	saturated-saturated ("SSS") triglycerides, i.e., referring to the chemical structure of the fatty acid moiety of each glyceride in the key triglyceride. As used herein, "S" refers to the stearic (St") or palmitic ("P") fatty acid residues of the glyceride molecule and ("U") refers to the oleic ("O") or linoleic ("L") fatty acid residues of the glyceride molecule.	15
20	Specifically, the lipid component of such particularly preferred composition contains at least about 70% of SOS triglycerides, and from about 4% to about 20% of combined SUU/UUU/SLS triglycerides, where the St:P weight ratio is about 0.8 or less. (These percentages are by weight of the lipid component, not by weight of total composition.) Preferably the lipid component contains about 8% or less of SLS triglycerides, about 9.5% or less of SSO triglycerides, about	20
25	2.5% or less of SSS triglycerides, and about 4% or less of other triglycerides. The lipid component of the present invention preferably is comprised entirely of a fat having a low St:P ratio (about 0.2 or less). A POP fat is particularly preferred. A preferred source of POP fat is	25
	through a triple stage solvent fractionation of palm oil. This particular lipid material employed may be selected in order to obtain desired product characteristics. These characteristics include such factors as rheology (mouth feel), appearance, flavor and compatibility with the pharmaceutical active.	
30	Among the lipid materials useful herein are those which are commercially available and commonly used in confectionery and other food products. Such lipid materials include, for example, cocoa butter, hydrogenated tallow, hydrogenated vegetable oils, and derivatives and mixtures	30
35	thereof Hydrogenated vegetable oils (such as hydrogenated palm kernel oil), cocoa butter, and cocoa butter substitutes are among the preferred useful lipid materials. Lipid materials among those useful in this invention are described in the following documents, all incorporated by reference herein: U.S. Patent 2,903,363, Farr, issued September 8, 1959; British Patent Specification 827,176, Best et al., published February 3, 1900; U.S. Patent 3,012,891, Best et al.,	35
40	issued December 12, 1961; U.S. Patent 3,093,480, Arnold, issued June 11, 1963; U.S. Patent 3,492,130, Harwood, issued January 27, 1970; U.S. Patent RE 28,737, Yetter reissued March 16, 1976; European Patent Application 23,062, Cotton et al., published January 28, 1981; U.S. Patent 4,276,322, Padley et al., issued June 30 1981; U.S. Patent 4,283,436, Soeters et al., issued August 31, 1981; U.S. Patent 4,364,868, Hargreaves, issued December 21, 1982; and	40
45	U.S. Patent 4,581,381, Morris et al., issued April 8, 1986; and U.S. Patent 4,594,259, Baker et al., issued June 10, 1986. Particularly preferred lipid materials are those that melt sharply at about 33°C (91°F). Such fats	45
	which melt "sharply" are those with melting profiles similar to cocoa butter, which is a solid at ambient temperatures, but is entirely liquid at a point just below mouth temperature (approximately 34°C).	
50	A commercially available material having such a preferred melting profile is Hydrokote, SP1, manufactured by Capital Cities Products Co. (Division of Stokely-VanCamp, Inc.). The solid fat index of this lipid material shows that the fat melts sharply at just below 34°C; being about 65% to 69% solid at about 21°C process is described in U.S. Patent 4,588,604, Baker et al., issued May 13, 1986 (incorporated by reference herein).	50
55	Dispersant Material:	55
	The compositions of this invention also contain a hydrophilic material, herein "dispersant material", which serves to aid dispersion of the pharmaceutical active and other materials of the composition in the mouth and/or stomach. Many dispersants among those useful herein are known in the pharmaceutical arts. Dispersant materials among those useful herein include sugars	
60	(such as sucrose, mannitol, sorbitol, dextrose, maltose, and lactose), starches and starch derivatives (such as corn starch and maltodextrin), microcrystalline cellulose, and mixtures thereof. Among the preferred dispersant materials useful herein are sucrose, sorbitol, mannitol, and	60
	mixtures thereof. 1300	

65 Emulsifier Material:

5	The compositions of this invention also contain one or more emulsification materials (herein individually and in mixtures referred to as "emulsifiers"). Emulsifiers may be characterized by their hydrophilic/lipophilic behavior. This behavior can be numerically expressed for a given emulsifier by its hydrophilic-lipophilic balance (HLB). The HLB value of an emulsifier can be determined experimentally or computed (particularly for polyoxyethylene ethers) from its structural formula. In general, emulsifiers with high HLB values are more hydrophilic, and tend to favor formation of oil-in-water emulsions, as opposed to emulsifiers with lower HLB values. Among the emulsifiers useful herein are the alkyl aryl sulfonates, alkyl sulfates, sulfonated	5
10	amides and amines, sulfated and sulfonated esters and ethers, alkyl sulfonates, polyethoxylated esters, mono- and diglycerides, diacetyl tartaric esters of monoglycerides, polyglycerol esters, sorbitan esters and ethoxylates, lactylated esters, propylene glycol esters, sucrose esters, and mixtures thereof.	10
15	Many such emulsifiers are known in the pharmaceutical arts. See, for example, M. Riegler, "Emulsions", The Theory and Practice of Industrial Pharmacy (L. Lachman, et al., ed. 1976), incorporated by reference here. Emulsifiers among those useful herein are also described in McCutcheon's Emulsifiers and Detergents, North American Edition (1983), incorporated by reference herein.	15
20	Preferably the emulsifier used in the present compositions includes a "low HLB emulsifier", i.e., an emulsifier having an HLB of from about 4 to about 10, more preferably from about 6 to about 10. Such low HLB emulsifiers are preferably included at a level of from about 0.1% to about 1%, more preferably from about 0.1% to about 0.5%. Also preferably, the present compositions are essentially free (e.g., containing less than about 0.1%) of emulsifiers having	20
25	HLB values less than about 4. Many low HLB emulsifiers are commercially available. Such emulsifiers among those useful herein include: Caprol 6G2S (hexaglycerol distearate), manufactured by Capital Cities Products Co.; Artodan (sodium stearoyl lactylates), manufactured by Grinsted Products; Myvatem 30 (monoglyceride diacetyl tartaric acid esters), manufactured by Eastman Chemical Products, Inc.; Polyaldo HGDS (hexaglycerol distearate) and Polyaldo TGMS (triglycerol monostearate), manufac-	25
30	tured by Glyco In.; and Span 60 (sorbitan monostearate) and Span 80 (sorbitan monosleate), manufactured by ICI Americas, Inc. The compositions of this invention also preferably contain one or more high HLB emulsifiers as a part of the emulsifier component. In particular, the present compositions preferably contain from about 0.1% to about 3%, more preferably from about 0.5% to about 2%, more preferably	30
35	from about 0.6% to about 1.5% of a nonionic emulsifier having an HLB of at least about 10. Preferably, the high HLB emulsifier has an HLB of at least about 11. Many such nonionic emulsifiers are commercially available. Such emulsifiers include, for example: Caprol PGE860 (Decaglycerol mono-dioleate), manufactured by Capital C.:ies Products Col; Hodag PSMS-20	35
40	(polyoxyethylene sorbitan) and Hodag SVO-9 (polyoxyethylene sorbitan 20 monooleate), manufactured by Hodag Chemical Corp.; Liposorb L-20 (polysorbate 20), Liposorb 0-20 (polysorbate 80), and Liposorb S-20 (polysorbate 60), manufactured by Lipo Chemicals, Inc.; Pluronic F69 (block copolymer of propylene oxide and ethylene oxide), manufactured by BASF Wyandotte Corp.; Santone 8-1-S (polyglycerol esters of fatty acids), manufactured by Durkee Industrial	40
45	Foods Group of SCM Corp.; and Tween 20 (polyoxyethylene 20 sorbitan monolaurate), Tween 60 (polyoxyethylene 20 sorbitan monostearate), Tween 80 (polyoxyethylene 20 sorbitan tristerate,	45
50	HLB ₁ × Wt% E ₁ . + HLB ₂ × Wt% E ₂ + HLB _n × Wt % E _n total HLB = Wt% E ₁ + Wt% E ₂ + Wt% E _n	50
55	wherein the composition contains "n" number of emulsifiers. The use of such high HLB emulsifiers to increase the efficacy of lipid-containing compositions is described in U.S. Patent Application Serial No. (P&G Case 3571, filed October 6, 1986 (incorporated by reference herein).	55
60	which is intended to have a physiologic effect on the human or lower animal to whom the composition is administered. Pharmaceutical active materials particularly useful in the chewable tablet formulations of this invention include those actives which become bioavailable and/or have	60
65	their site of action in the mouth or stomach. The rapid dispersion of such active materials in the saliva, as afforded by the present chewable tablets, is particularly advantageous. Among such	65

5

10

15

20

25

35

50

55

60

65

active materials are the analgesics, such as aspirin and acetaminophen, and materials used in the treatment of gastrointestinal disorders.

Among the pharmaceutical active materials particularly useful in the compositions of this invention are the bismuth salts and the metallic antacid salts. Such bismuth salts include, for 5 example, bismuth aluminate, bismuth citrate, bismuth nitrate, bismuth subcarbonate, bismuth subgalate, bismuth subsalicylate, and mixtures thereof. A particularly preferred bismuth salt is bismuth subsalicylate. Metallic antacid salts useful herein include, for example, aluminum carbonate, aluminum, hydroxide, aluminium phosphate, aluminium hydroxycarbonate, dihydroxy aluminum sodium carbonate, aluminum magnesium glycinate, dihydroxy aluminum amino acetate, dihydroxy aluminum aminoacetic acid, calcium carbonate, calcium phosphate, aluminum magnesium hydrated sulfates, magnesium aluminate, magnesium alumino silicates, magnesium carbonate, magnesium glycinate, magnesium hydroxide, magnesium oxide, magnesium trisilicate, and mixtures thereof. Aluminum magnesium hydroxide sulfate (also known as magaldrate) is a preferred metallic antacid salt useful herein.

Optional Components

The compositions of this invention may also contain pharmaceutically-acceptable optional components which modify the physical and/or therapeutic effects of the composition. Such optional components may include, for example, emulsifiers, binders, lubricants, glidants, colorants, flavors and sweeteners. Such components are generally described in Marshall, "Solid Oral Dosage Forms", Modern Pharmaceutics, Volume 7, (Banker and Rhodes, editors), 359–427 (1979), incorporated by reference herein, and W. Gunsel, et al., "Tablets", The Theory and Practice of Industrial Pharmacy (L. Lachman, et al., editors, 2 ed.), 321–358 (1976), incorporated by reference herein.

Pharmaceutically-acceptable oils may be included to obtain a desired measured viscosity (as discussed below), preferably at levels of from about 0.1% to about 2%, more preferably from about 0.1% to about 1%. Such materials include, for example, vegetable oils, mineral oils and mixtures thereof. Certain emulsification materials, discussed above, may also be oils. However, as also discussed below, it is preferred that the levels of oils and other liquid materials in these 30 compositions be minimized.

As will be appreciated by those skilled in the art, the lipid base material of the present composition may be present in any of a number of crystal forms, or polymorphs, depending upon the particular lipid material used. For compositions wherein POP fat is utilized as the lipid base material, it is preferred that the fat be present in the beta-prime-2 or beta-3 polymorph state. The crystal structure of the lipid bse material useful herein may be affected by a variety of factors, as can be ascertained by one of skill in the art. Such factors include the presence of solids in the composition, the resence of emulsifiers, he processing conditions (particularly cooling temperatures and rates), and the particular lipid base material employed.

A preferred optional component in molded tablets of this invention (i.e., compositions that are formed upon solidification of a heated liquid composition after pouring into a suitable mold) is a "tempering aid". Such materials aid in the formation of a desired crystal structure for the lipid components of the present composition, such that the composition has a desired uniform, smooth, non-gritty texture and appearance. Tempering aids are preferably included at a level of from about 0.2% to about 2%. Among tempering aids useful herein are mixtures of mono- and diglycerides, such as Dur-Em 127 (manufactured by Durkee Foods, Division of SCM Corporation) and triglyceride mixtures, such as Cessa 60 (manufactured by Friwessa).

Also preferably, the compositions of this invention contain less than about 1% of materials that are liquid at ambient conditions in addition to any liquid components of the lipid material, it has been found that the level of such liquid materials may affect the storage stability of these compositions. More preferably these compositions contain less than about 0.5% of such additional liquid materials.

Other preferred optional components useful herein include flavorants and sweetners, at levels of from about 0.01% to about 1.0%. Colorants may be included at typical levels of from about 0.01% to about 0.5%.

As stated above, the present compositions may be coated, to provide a coated unit dosage form. The coated compositions of the invention comprise a lipid-containing composition of this invention, covered with from about 10% to about 50%, preferably from about 10% to about 30%, (by weight of final coated composition) of a solid, water-soluble coating material having a melting point greater than about 45°C. Such coated compositions preferably are in unit-dosage

60 form, i.e., containing an amount of pharmaceutical active material suitable for administration to a human subject, in one dose, according to good medical practice. The coated compositions of this invention preferably contain from about 0.5 to about 2.5 grams, preferably from about 1.0 to about 2.0 grams, of the lipid-containing composition of this invention.

Coating materials, and methods, among those useful herein are well known in the pharmaceuti-65 cal arts. See, for example, W. Gunsel, et al., "Tablets", The Theory and Practice of Industrial

Pharmacy (L. Lachman, et al., editors, 2d ed.) 321–358 (1976), incorporated by reference herein. Preferred coatings and materials are described in U.S. Patent Application Serial No. (P&G Case 3573), filed October 6, 1986, incorporated by reference herein.

5 Methods 5 The chewable tablet compositions of this invention may be made by molding techniques. Molding techniques generally involve admixture of components in an essentially liquid form, followed by pouring into a desired tablet mold and cooling to a solid, or semi-solid form. The compositions of this invention are preferably in molded form. 10 The lipid base material used in molded compositions of the present invention is preferably in a 10 stable crystal form, such that the composition is comprised of stable crystals less than about 5 microns, preferably from about 1 to about 2 microns, in size, and the composition has a uniform, smooth, non-gritty appearance and rheology. Such parameters, and the factors which influence them, are analogous to parameters that are well known in the chocolate confectionery 15 arts. As discussed above, materials may be added to the present compositions which aid in 15 obtaining a preferred, stable crystal structure, or "temper". Processing conditions for making molded compositions are also critical, and are preferably controlled to yield a preferred tempered composition. Such "tempering", for compositions utilizing POP fat as a lipid base material, typically involved cooling of the product in liquid form, to a temperature of approximately 22°C. 20 This cooling induces formation of a variety of crystals of different melting points. The compo-20 sition is then heated, with stirring, to approximately 29.5°C, melting the undesired lower-melting crystals. (The fluid product at this point is thereby "seeded" with higher-melting crystals.) The fluid product is then poured into molds, vibrated to remove air bubbles, and slowly cooled to solidify the composition into a product having the desired crystal form. 25 The molded, uncoated compositions of this invention preferably have a viscosity (herein "mea-25 sured viscosity") of less than about 10,000 centipoises (cps), while in liquid mixture (melted) at approximately 40°C. More preferably, the measured viscosity is less than about 8,000 cps, more preferably less than about 5,000 cps. This measured viscosity may be measured using a Brookfield Viscometer, Model RVT/2 with Helipath (Spindle C, at 10 rpm). The uncoated product 30 is first melted, using a water bath, at a temperature of approximately 50°C. The product is then 30 mixed for approximately one hour, using a paddle mixer (such as a Model K4553 Kitchen Aid Mixer, at speed setting #2). The product mixture is cooled slowly (over a period of approximately 30 minutes), while mixing, to a temperature of approximately 40°C. The mixing is stopped, and the viscometer spindle is then inserted into the product mass. The viscosity 35 reading is taken at equilibrium, or after lapse of 30 seconds, whichever comes first. 35 The product measured viscosity may be obtained by selection of materials and processing conditions. For example, the desired measured viscosity hay be obtained by selection of the type and level of lipid material, emulsifiers, particulate materials (active material and dispersant material) and optional materials. The measured viscosity of the present compositions may be 40 obtained by control of processing conditions, including (for example) milling of materials, order of addition of materials, and tempering conditions. In particular, the particle size of particulate materials of the present compositions are controlled by selection of materials and/or by selection of processing conditions. (As used herein "particulate materials" include the pharmaceutical active material, dispersant material, and any optional 45 components that are not substantially soluble in the lipid material or other components of the composition.) The mean (by volume) particle size of the particulate materials is in the range of from about 4 microns to about 10 microns, preferably from about 6 microns to about 10 microns. Less than about 10% of the particulate materials have a particle size greater than about 30 microns. (As used herein, "particle size" of a particulate refers to the diameter of a sphere 50 having a volume equal to that of said particulate.) 50 The particle size of the uncoated compositions of this invention may be determined using a Malvern 2600/3600 Particle Sizer (manufactured by Malvern Instrument Company). The uncoated composition is melted in mineral oil, at approximately 40°C. The mixture is then dispersed using a high speed mixer, for at least about 5 minutes. After mixing, several drops of the product 55 mixture are placed in the Particle Sizer, using mineral oil as the dispersant. The product mixture is mixed in the apparatus at a medium speed setting. The following non-limiting Examples illustrate the compositions, processes and uses of the

60 EXAMPLE I

present invention.

ひ間 おかまりとうない 持ちれたおきました

A coated antacid composition according to this invention was made comprising:

	Component	8 Bulk Composition	§ Final Tablet		
	POP fat ¹	34.009	28.908		
Į	sucrose	31.640	26.894	E	
	magaldrate ²	31.640	26.894	_	
	simethicone	0.991	0.842		
10) Span 80 ³	0.475	0.406	10	
	Tween 60 ⁴	0.148	0.126	10	
	sucrose monoester ⁵	0.487	0.414		
15	sodium stearoyl		•	15	
	lactylate ⁶	0.009	0.008		
	Dur-Em 127	0.498	0.423		
20	peppermint oil	0.100	0.085	20	
	•	100.000			
	(Coating)				
25	Neosorb P100T ⁸		8.700	25	
	lycasin		4.100	,	
	mannitol		2.200		
30			100.000	30	
35	 lipid base material, comprising approximately 88% SUS triglyceride, with an St:P ratio of approximately 0.13 aluminum magnesium hydroxide sulfate, antacid, active material sorbitan molooleate emulsifier, HLB=4.3, mnufactured by ICI Americas, Inc. polyoxyethylene (20) sorbitan monooleate emulsifier, HLB=14.9, manufactured by ICI Americas, Inc. emulsifier, HLB=15.0 				
40	 6. emulsifier, HLB=9.0 7. tempering aid mixture of mono- and diglycerides, HLB=2.8, manufactured by Durkee Foods, Division of SCM Corporation. 8. fine sorbitol powder, manufactured by The Roquette Corporation 				
45	and heating to approximately 40°C. Separately, approximately 55% of the POP fat was melted at approximately 40°C, and approximately 10% of the Span 80 was added, and mixed. The POP-fat mixture was then added to the active/sugar mixture, maintaining the temperature at approximately 40°C., and mixed for approximately 45 minutes. The mixture was passed through a 4-mile			45	
80	material and the powdered materials. The 4 mill rollers were at temperatures of approximately 27°C, 21°C, 21°C and 21°C, respectively. Separately, the remaining portion of POP (approximately 45% of the original questing was				
	admixed with the remaining portion of Span 80 (approximately 90% of the original quantity), the Dur-Em, and the sodium stearyl lactylate emulsifier, for approximately 10 minutes, at a temperature of approximately 50°C. The sucrose monoester and Tween 60 were dissolved in ethanol, and then added to the composition. The peppermint oil and simethicone were then added, and the compositions mixed for approximately 45 minutes, maintaining the temperature at approximately 50°C.				
	mately 50°C. The milled POP mixture was then added to this POP/emulsifier mixture, and mixed for approximately 15 minutes. The composition was then cooled to approximately 22°C, and tempered by rapidly raising the temperature to approximately 29.5°C, forming seed crystals. The composition was then poured into tablet molds and allowed to solidify. The average tablet weight was approximately 2.2 g. The tablets were then coated by placing them in a conventional coating pan apparatus. A				
00	portion of the lycasin was a	added, and the tablets evenly we QOINTON	etted. The mannitol was then added,	65	

45

and the tablets mixed for approximately 10 minutes, and then dried for approximately one hour. The tablets were then coated with lycasin and Neosorb, following the same procedure, and dried for approximately 12 hours.

A coated antacid tablet, comprised as above, was administered to a human subject experienc-5 ing heartburn, and was effective in reducing the severity of symptoms. The average HLB of the lipid containing core composition of this Example is calculated to be approximately 8.1. The measured viscosity of the lipid-containing core composition is found to be approximately 6,600 cps.

10 EXAMPLE II

A coated antacid composition according to this invention is made comprising:

	Component	§ Bulk Composition	% Final Tablet	
15	POP fat	28.0	23.80	15
	sucrose	15.0	12.75	
	sorbitol	15.0	12.75	
20	calcium carbonate	40.0	34.00	20
	sucrose monoester	1.0	0.85	
	Tween 60	0.5	0.43	
25	flavorant	0.5	0.42	25
		100.00		
30	(Coating)			30
	sorbitol		3.00	
	corn syrup		1.00	
35	sucrose		10.50	35
	maltrin		0.50	
	•		100.00	

A coated antacid composition, comprised as above, is made by a method analogous to that described in Example I. The tablets are formed into unit dosage tablets, containing approximately 2.2 grams of the lipid-containing composition. The average HLB of the lipid-containing core composition of this Example is calculated to be approximately 14.9.

45 EXAMPLE III

A coated antacid composition according to this invention was made comprising:

Component	N. D. H. Campanidian		
	Bulk Composition	§ Final Tablet	
POP fat	35.942	30.000	
sucrose	26.119	21.800	
magaldrate	35.703	29.800	
Cessa 60 ¹	0.994	0.830	•
Myrj 52 ²	0,503	0.420	1
Caprol PGE 860 ³	0.395	0.330	1
Polyaldo HCDS	0.252	0.210	
flavorant	0.092	0.077	
	100.000		
(Coating)			
sorbitol solution ³		10.700	
lycasin		1.060	
mannitol		4.023	
Klucel EF ⁶		0.750	
		100.000	
5. 70% solution6. hydroxypropyl cellulose g	um, manufactured by Hercu	, manufactured by Glyco, Inc. les Chemical Company.	
6. hydroxypropyl cellulose g A coated composition, com described in Example I.	um, manufactured by Hercu		
6. hydroxypropyl cellulose gi A coated composition, com described in Example I. EXAMPLE IV	um, manufactured by Hercu	les Chemical Company.	
6. hydroxypropyl cellulose gi A coated composition, com described in Example I. EXAMPLE IV	um, manufactured by Hercu nprised as above, was made	les Chemical Company.	
6. hydroxypropyl cellulose grade A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat*	um, manufactured by Hercul apprised as above, was chade according to this invention is	les Chemical Company.	
6. hydroxypropyl cellulose graduated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat*	um, manufactured by Hercular oprised as above, was made occording to this invention is by Weight	les Chemical Company.	
6. hydroxypropyl cellulose gradescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat*	um, manufactured by Hercular reprised as above, was made according to this invention is \$ by Weight 34.00	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate	um, manufactured by Hercular opprised as above, was made according to this invention is § by Weight 34.00 1.50	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose	um, manufactured by Hercular reprised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate	um, manufactured by Hercular reprised as above, was made according to this invention is § by Weight 34.00 1.50 30.93 30.93	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester	um, manufactured by Hercular opprised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860	um, manufactured by Hercular prised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00 0.90	les Chemical Company.	,
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester	um, manufactured by Hercular recording to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00 0.90 0.50	les Chemical Company.	,
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester Tween 60 Span 80 flavorant	um, manufactured by Hercular opprised as above, was made occording to this invention is § by Weight 34.00 1.50 30.93 30.93 1.00 0.90 0.50 0.10	les Chemical Company.	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester Tween 60 Span 80 flavorant	um, manufactured by Hercular prised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00 0.90 0.50 0.10	les Chemical Company. e by a method analogous to that made comprising:	
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester Tween 60 Span 80 flavorant	um, manufactured by Hercular prised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00 0.90 0.50 0.10	les Chemical Company.	•
A coated composition, comdescribed in Example I. EXAMPLE IV An uncoated composition a Component Hydrokote SP1 fat* vegetable oil sucrose magaldrate simethicone Caprol PGE 860 sucrose monoester Tween 60 Span 80 flavorant *lauric lipid mate Co.	um, manufactured by Hercular prised as above, was made according to this invention is 8 by Weight 34.00 1.50 30.93 30.93 1.00 0.90 0.50 0.10	les Chemical Company. by a method analogous to that made comprising: Capital City Products	

An uncoated composition according to this invention is made comprising:

		and the time the time to the t	
	Component	% by Weight	
5	POP fat	35.00	5
	mannitol	15.76	
	bismuth subsalicylate	25.95	
10	calcium carbonate	20.00	10
	hexaglycerol distearate	0.25	
	polyoxyl (40) stearate	0.50	
15	sucrose monoester	0.48	15
	flavorant	1.60	
	sweetener	0.20	
20	colorant	0.26	20
25	composition per tablet. Two tablet lessening the severity of symptoms calculated to be approximately 14.6	es above, are made containing approximately 1.1 grams of s are administered to a human subject experiencing nausea, s. The average HLB of the composition of this Example is 6.	25
30	26°C to about 37°C; (b) from about 10% to about 50 (c) from about 0.1% to about 3	0% of a lipid material having a melting point of from about 0% of a particulate dispersant material;	30
35	wherein the particulate materials in microns to about 10 microns, with 30 microns in size.	said composition have a mean particle size of from about 4 less than about 10% of said particulates greater than about	35
40	terials in said composition have a r microns. 3. A molded pharmaceutical cor less than about 10,000 cps at abo	mposition according to Claim 1, wherein the particulate mamean particle size of from about 6 microns to about 10 mposition according to Claim 1, having a measured viscosity out 40°C. mposition according to Claim 3, having a measured viscosity	40
45	 less than about 5000 cps at about A molded pharmaceutical cor a melting point of from about 32°C A molded pharmaceutical cor melts sharply at about 33°C. 	40°C. mposition according to Claim 3, wherein said lipid material has to about 35°C. mposition according to Claim 5, wherein said lipid material	45
50	material is present at a level of from 8. A molded pharmaceutical corpersant material is present at a level of from the following present at a level of from the	mposition according to Claim 5, wherein said lipid base m about 25% to about 40%. mposition according to Claim 7, wherein said particulate disell of from about 20% to about 35%. mposition according to Claim 8, containing a low HLB emulsi-	50
55	10. A molded pharmaceutical co- emulsifier is present at a level of fr	emposition according to Claim 3, additionally comprising from	55
60	12. A molded pharmaceutical co tempering aid.	omposition according to Claim 3, additionally comprising a omposition according to Claim 12, containing less than about	60
65	14. A molded pharmaceutical cocal active material is useful in the table. A molded pharmaceutical cocal active material is useful in the table.	omposition according to Claim 12, wherein said pharmaceuti- reatment of gastrointestinal disorders. omposition according to Claim 14, wherein said pharmaceuti- 8 1 0 7 2 0 4	65

cal active material is a metallic antacid salt.

- 16. A molded pharmaceutical composition according to Claim 14, wherein said pharmaceutical active material is a bismuth salt.
- 17. A coated pharmaceutical composition, in unit dosage form, comprising from about 50%
 5 to about 90% of a composition according to Claim 1, and from about 10% to about 50% of a coating material.

Published 1988 at The Parent Office, State House, 66/71 High Holborn, London WC1R 4TP. Further copies may be obtained from The Patent Office, Sales Branch, St Mary Cray, Orpington, Kent BR5 3RD. Printed by Burgese & Son (Abingdon) Ltd. Con. 1/87.